

SILICONE RUBBER BRAIDED TUBE

NON-HEAT SHRINK

RoHS COMPLIANT

HI TEMPERATURE



RUB-300 is a high temperature resistant silicone rubber tube with a fiberglass braid surrounding the exterior of the tube. This product has excellent flexibility and excellent arc resistance.

RUB-300 Applications

This product is used in various applications such as protection in household appliances, light fixtures, machinery, and electronic instruments where components are exposed to high temperatures.

Characteristics

Operating Temperature: -60° to 200° Celsius

Environmentally Friendly

Colors: Standard Packages Available in Black & White, Colors Available Upon Request

Specifications

Gamma Part No.	Standard Size					
	Inner Diameter		Min Wall Thickness		Avg Wall Thickness	
	mm	inch	mm	Inch	mm	inch
RUB-300-1	1	0.039	0.60	0.024	0.80	0.031
RUB-300-2	2	0.079	0.60	0.024	0.80	0.031
RUB-300-3	3	0.118	0.80	0.031	1.00	0.039
RUB-300-4	4	0.157	0.80	0.031	1.00	0.039
RUB-300-5	5	0.197	0.80	0.031	1.00	0.039
RUB-300-6	6	0.236	1.00	0.039	1.20	0.047
RUB-300-7	7	0.276	1.00	0.039	1.20	0.047
RUB-300-8	8	0.315	1.00	0.039	1.20	0.047

RUB-300-9	9	0.354	1.20	0.047	1.50	0.059
RUB-300-10	10	0.394	1.20	0.047	1.50	0.059

Color Code: 0=BLK, 1=BRN, 2=RED, 3=ORN, 4=YLW, 5=GRN, 6=BLU, 7=VIO, 8=GRY, 9=WHT, X=CLR

P/N Example: RUB-300-1-0 = Black 1mm Tubing

Property of Gamma Electronics
www.gammaelectronics.net