



## HIGHLY FLEXIBLE SKID PROOF HEAT SHRINKABLE TUBE

**SHRINK RATIO: 2:1**

**SKID RESISTANT**

**RoHS**

**E306685**

**SKID-100** is a highly flexible, skid resistant, environment friendly, heat shrinkable tube.

Bright colors enhance the appearance of finished products such as handle bars, fishing tackle, exercise equipment, etc. This product is designed to enhance friction when being held. Order **SKID-125** with bright colored stripes for a little variety in the appearance fishing tackle



### **SKID-100 Applications**

---

Comfortable Grip

Skid Resistant

Bright Colors for Product Identification

Offers Protection against Moisture

Fast Shrinkage for Easy Application

### **Characteristics**

---

Operating Temperature: -55° to 105° Celsius

Shrink Temperature: Start at 70° C; Completely Shrunk 110° C

Shrink Ratio: 2:1

Colors: Black, Red, Yellow, Green, Blue (Other Colors Available per Request) Also Available with Cool Stripes

## Specifications

Gamma Part No.  W/ Size					Standard
	As Supplied		After Recovery		Packaging
	ID (mm)	Wall Thickness (mm)	Max ID (mm)	ID (mm)	4FT Lngth
SKID-100-15mm	15	0.45	8	0.85	200'
SKID-100-20mm	20	0.50	11	0.90	200'
SKID-100-22mm	22	0.50	12.5	0.90	200'
SKID-100-25mm	25	0.50	14.5	1.00	100'
SKID-100-28mm	28	0.50	15.5	1.00	100'
SKID-100-30mm	30	0.60	17.5	1.20	100'
SKID-100-35mm	35	0.60	20	1.20	50'
SKID-100-40mm	40	0.60	23	1.20	50'
SKID-100-45mm	45	0.65	25	1.25	50'
SKID-100-50mm	50	0.65	28	1.25	50'

Color Code: 0=BLK, 1=BRN, 2=RED, 3=ORN, 4=YLW, 5=GRN, 6=BLU, 7=VIO, 8=GRY, 9=WHT, X=CLR

P/N Example: SKID-100-25mm-0 = Black 25mm Black Skid Resistant Tubing

P/N Example: SKID-125-25mm-0/2 = Black w/ Red Stripes 25mm Skid Resistant Tubing

Property of Gamma Electronics

[www.gammapelectronics.net](http://www.gammapelectronics.net)